



BRAKE CLEANER

Revision: 12/03/2009

Page 1 of 1

Technical data:

Base	Based on solvents
Consistence	Liquid
Density	0,69 g/mL
Viscosity at 20℃	1 mPa.s
Flash point	< 20℃
Spray rate	4 gr/sec
Acidity pH	Neutral
Solubility in water	Not soluble
VOC content	97%
Propellant	CO ₂

Product:

Powerful, fast-drying cleaner for brake and clutch parts.

Applications:

Removes excess brake fluid, excess oil, dirt, etc. quickly. Prevents squeaking brakes and clutch slipping. Easy to apply from all angles and does not corrode metals.

Characteristics:

- Cleans and degreases
- Does not drip
- Quick-drying
- Does not corrode metals
- Prevents squeaking sounds
- Aerosol can be used in any angle (360)

Packaging:

Colour. transparent

Packaging: aerosol can of 400 ml / 6 units per box

Shelf Life:

3 years in unopened packaging in a cool and dry storage place at temperatures between $+5^{\circ}$ and $+25^{\circ}$.

Instructions:

Shake can well. Spray sufficient product on the parts to be cleaned and let it work for a few seconds. If necessary, wipe clean with an absorbing cloth. In case of extensive carbon contamination, repeat the procedure. Do not use on rubber, plastics or painted parts. Make sure there is sufficient ventilation when using the product.

Health and Safety Recommendations:

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsability for the results obtained. In every case it is recommended to carry out preliminary experiments.

Everdongenlaan 18-20 Fax: +32 (0)14-42.65.14 2300 Turnhout, Belgium www.soudal.com