
Mud Remover

Revision: 13/09/2017

Page 1 from 1

Technical data

| | |
|-------------------------|--------------------------------|
| Basis | Water with specific detergents |
| Consistency | Fluid |
| Density | 1,00 g/ml |
| Application temperature | 5 °C → 35 °C |

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Mud Remover is a ready-to-use, professional, powerful cleaner for efficient cleaning of bicycle frames, wheels and handlebars.

Remarks

- Mud Remover is slightly alkaline.
- We strongly recommend not to apply the product in full sunlight as it will dry very fast.

Properties

- Remove dried dirt, sand and dust
- Excellent cleaning properties
- Ready for use
- Not flammable
- Does not contain harmful solvents nor acids
- 100% biodegradable

Applications

- Clean stubborn dirt and mud on bicycle frames, wheels and handlebars.
- Suitable for matt, painted and unpainted surfaces as well as carbon.

Packaging

Colour: green

Packaging: 1 L bottle

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Application method

Application method: Spray Mud Remover at the heavily polluted parts. Let the foam layer work for a few minutes. Stubborn dirt or mud can possibly be rubbed off with a sponge. Then thoroughly rinse off with plenty of water and dry with a dry cloth or blow dry.

Health- and Safety Recommendations

Take the usual labour hygiene into account.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.