

SOUDAL PRO GAPS FILL & PAINT

Technical Data

Basis	Acrylic dispersion
Consistency	Paste
Curing system	Physical drying
Skin formation* (20°C/65% R.H.)	Ca. 20 min
Density	Ca. 1.67 g/mL
Maximum allowed distortion	10 %
Shrinkage (DIN52451)	Ca. 15%
Temperature resistance**	-20 °C → 80 °C
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

** This information relates to fully cured product

Product description

Soudal Pro Gaps Fill & Paint is a high-quality plasto-elastic one-component joint sealant based on acrylic dispersion.

Properties

- Very easy to apply
- Colourfast and waterproof after drying
- Can be painted over after drying
- Very good adhesion on many porous surfaces and aluminium
- Good weather and UV resistance after drying
- Interior and exterior use
- Paintable within 20 minutes

Applications

- Joints on window sills, between plinths and walls, between masonry, ...
- Joints with movement till max. 10%
- Filling of gaps and cracks in concrete, plasterwork and ceiling.
- Sealing skirting boards, cornices, window frames, staircases, architraves, trims and coving.

Packaging

Colour: white

Packaging: 300 mL cartridge

Shelf life

At least 12 months in original, unopened packaging in a cool and dry storage place with temperature between +5°C and +25°C. Protect from frost.

Substrates

Substrates: all usual porous building substrates, including timber, MDF, particle board, plywood, fibre cement sheet, plasterboard, concrete, masonry including brick and block work, cement render, tiles, ceramics, aluminium, etc...

Nature: rigid, clean, free of dust and grease, dry

Surface preparation: For optimal adhesion and in critical applications, we recommend to follow a pretreatment procedure. Prepare highly porous surfaces with a diluted Soudal Pro Gaps Fill & Paint. Add 1 part Soudal Pro Gaps Fill & Paint with 2 parts water.

We recommend a preliminary adhesion and compatibility test on every surface.

Joint dimensions

	JOINT		BONDING
	Width	Depth	Width
Min	1 mm	5 mm	NA
Max	10 mm	10 mm	NA

*Recommendation for sealing: width = depth
Use PE backing rod in large joints to avoid 3-point adhesion.*

Application method

Refer to the current Technical Data Sheet on our website prior to use.

Do not apply when rain or frost is imminent during curing process.

Application method: With manual- or pneumatic caulking gun. Finish with a spatula or filling knife.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case, it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

SOUDAL PRO GAPS FILL & PAINT

Cleaning: Clean with water or with Soudal **Swipex**, immediately after use. Cured Soudal Pro Gaps Fill & Paint can only be removed mechanically.

Finishing: With water before skinning. Tool within 20 minutes of application

Repair: With the same material.

Painting: use sufficient flexible sealant when painting

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult label and material safety data sheet for more information.

Remarks

- Do not use in applications where continuous water immersion is possible.
- Paintable with most paints.
- The paint must be sufficiently elastic to allow application on a plasto-elastic sealant.
- Given the great diversity in available paints, it is recommended to do a compatibility test prior to application.
- When using different reactive joint sealants, the first joint sealant must be completely hardened before the next one is applied.

Environmental clauses

Leed regulation:

Soudal Pro Gaps Fill & Paint conforms to the requirements of LEED. Low –Emitting Materials: Adhesives and Sealants. SCAQMD rule 1168. Complies with USGBC LEED 2009 Credit 4.1: Low-Emitting Materials – Adhesives & Sealants concerning the VOC-content.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case, it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.